

Die collars (K and LK types)

are used for capturing and subsequent extraction of the drilling pipes or tubing strings, that were left in the well, by cutting-in and screwing on outer surface of the pipe.

The difference between die collar type K and type LK is the pin thread for the re-entry guide connection.



| Type | Connecting threads GOST 28487 | Dimensions, mm | | Weight, kg |
|-----------|----------------------------------|----------------|--------|---------------|
| | | Outer diameter | Length | |
| K 58-40 | 3-66 | 90 | 490 | 15 |
| K 70-52 | 3-66 | 90 | 510 | 14 |
| K 85-64 | 3-76 | 102 | 550 | 18 |
| K 100-78 | 3-88 | 122 | 595 | 26,5 |
| K 110-91 | 3-101 | 132 | 555 | 26,5 |
| K 125-103 | 3-121 | 148 | 560 | 31 |
| K 135-113 | 3-133 | 170 | 635 | 41 |
| K 150-128 | 3-147 | 194 | 655 | 70 |
| K 174-143 | 3-171 | 220 | 800 | 98 |

Die collars (KS and LKS types)

are used for capturing and subsequent extraction of the drilling pipes or tubing strings, that were left in the well, by cutting-in and screwing on outer surface of the pipe.

The difference between die collar type K and type LK is the pin thread for the re-entry guide connection.

| Type | Dimensions, mm | | Weight, kg |
|-------|----------------|--------|------------|
| | Outer diameter | Length | |
| KS54 | 73 | 330 | 8 |
| KS70 | 90 | 380 | 13 |
| KS85 | 106 | 390 | 17 |
| KS100 | 122 | 450 | 20 |
| KS115 | 140 | 460 | 24 |
| KS125 | 148 | 440 | 25 |
| KS150 | 180 | 545 | 53 |
| KS160 | 194 | 505 | 45,5 |
| KS180 | 220 | 560 | 78 |
| KS195 | 220 | 575 | 57 |
| KS210 | 245 | 650 | 66 |
| KS235 | 274 | 480 | 68 |
| KS260 | 299 | 495 | 72 |